



	仪表数据表 INSTRUMENT DATA SHEET			
	惰性气体密封系统			
	INERT BLANKETING SYSTEM			
	合同号 CONT. NO.			
位号 TAG NO.				
用途 SERVICE			储槽压力控制	
P&ID号 P&ID NO.				
设备位号 EQUIP. NO.			醋酸二期槽区储罐	
操作条件 OPERATING CONDITIONS				
工艺介质 PROCESS FLUID			醋酸、甲醇	
操作压力 OPER. PRESS. MPa(G)			0.5KPa	
操作温度 OPER. TEMPER. °C			32	
贮槽容积 TANK VOLUME			醋酸800m3、甲醇500m3	
泵输出流量 PUMP OUT RATE			150m3/h	
氮气压力 MAX DIFF PRESSURE			700KPaG	
贮槽放空阀设定值 TANK VENT SETTING			6"H2O	
仪表规格 METER SPECIFICATION				
产品代号 PRODUCT		■		
执行器 ACTUATOR		☐ 1 C.S W/TEFLON DIAPH ■ 2 316L/TEFLOW DIAPH		
		☐ 3 C.S W/BUNA-N DIAPH ☐ 4 316L/BUNA-N DIAPH		
阀体、阀盖和内件 BODY, BOUNET & TRIM		■ 316 L ☐ 316 ☐ 304L ☐ 304		
填料 ELASTOMERS		☐ B BUNA-N ☐ C CHEMRAZ ☐ E FDA-EPDM		
		☐ F FDA-BUNA-N ■ V VITON		
连接尺寸 CONNE CTIONS		☐ 1 1"NPT ■ 1"-150# THREADED FLG 法兰与本体1寸NPT螺牙连接		
控制压力范围 CONTROL PRESS RANGE		■ 1 0.5~8in.WC ☐ 2 4~10 in.WC		
		☐ 3 8~15 in.WC ☐ 4 0.5~1.5psi		
入口操作范围 INLET OPERATING RANGE		☐ A 25~50psi ■ B 51~120psi		
		☐ C 120~200psi		
备注： 要求阀门一进口双出口，可以根据 现场实际情况，水平安装和垂直安 装自由切换，下图法兰间距A为 140mm。		■ A SS FILTER ☐ B INLET PRESS. GAGE. SS		
		☐ C CONTROL PRESS. GAGE DWYER ☐ D CONTROL GAGE. SS 4"WC		
		☐ G SENSING LINE PURGE-SS ☐ J MAIN LINE PURGE-SS		
		☐ K PRESS. SWITCH. X=PROOF ☐ L MAIN LINE CHECK VALVE-SS		
		☐ M MTG. KIT. SS ☐ P DIAGNOSTIC & INLET GAGE-SS ☐ O NONE		
  注：标准外部取压				